

25mm THICK CEMENT SAND SCREEDING ON SLAB (BY OTHERS)

- DRAIN TO P&D DRAINAGE (BY OTHERS) 50mm THICK CEMENT SAND SCREEDING WITH EM LATHING REINFORCEMENT AND COLOUR

MIN. 50mm RIGID THERMAL INSULATION

1.5mm HYDROLINK "SPI" HT100F POLYUREA

WATERPROOFING MEMBRANE WITH ONE COAT OF EPOXY 1545 PRIMER (BY KESFORD)

FLOOR HARDENER (BY OTHERS)

BOARD (BY OTHERS)

PIPE (BY OTHERS)

1.5mm HYDROLINK "SPI" HT100F POLYUREA WATERPROOFING MEMBRANE WITH ONE COAT OF EPOXY 1545 PRIMER (BY KESFORD)

1.8mm THK. ALUMINIUM FLASHING (BY OTHERS)

MIN. 25mm WATERPROOFED CEMENT SAND ANGLE

50mm THICK CEMENT SAND SCREEDING WITH EM LATHING REINFORCEMENT AND COLOUR FLOOR HARDENER (BY OTHERS)

MIN. 50mm RIGID THERMAL INSULATION BOARD

25mm THICK CEMENT SAND SCREEDING ON SLAB